

PCA Conserve & Seal™

CONSERVE & SEAL™ is a ready to use penetrating treatment that stabilises masonry and natural stone surfaces by replacing the natural binding materials lost due to weathering over time.

CONSERVE & SEAL™ has been formulated and laboratory tested to penetrate deeply into the deteriorated surfaces to bind the stone particles together. Ideal for both internal and external use.



- SANDSTONE
- TRAVERTINE
- GRANITE

- LIMESTONE
- TERRACOTTA
- CONCRETE

- BRICKS
- WET & DRY CAST PAVERS

- Strengthens deteriorated stone
- Allows surface to breathe
- Low molecular for optimum penetration
- Quick dry formulation
- Clear and invisible protection
- Permits vapour transmission
- Internal and external use
- User friendly and easy to apply
- Mould and mildew resistant
- Binder formed acid resistant

SURFACE PREPARATION AND APPLICATION / DIRECTION FOR USE

Surfaces should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence and laitance before applying Conserve & Seal™.

1. Ensure the surface is clean and dry
2. Surface sealer and repellents must be removed prior to application.
3. Cover surfaces not intended to be treated.
4. Saturate an even first coat using a low-pressure sprayer, lambswool applicator, paint brush or dipping. It is recommended to use a pump sprayer on rough surfaces.
5. Allow sealer to penetrate the surface for 5 - 15 minutes.
6. Typical treatments involve 2 - 3 cycles (6-9 separation application)
7. Please allow 20 - 60 minute curing time between each cycle.
8. After final application, thoroughly wipe all excess sealer with clean and absorbent towels.
9. If a second treatment is required, allow 2 - 3 weeks curing time following the initial treatment.
10. It is important that no water comes into contact with newly treated surfaces for at least 2-3 days after application.
11. Clean tools used during application with methylated/ white spirits or solvents.

Always do a test first in an inconspicuous area to ensure suitability and satisfactory results.

COVERAGE

Application rate depends on the degree of the deterioration of the surface, temperature and method of application. It ranges between 0.5 - 4 sqms per litre.

MAINTENANCE

Use STONE SOAP™ for daily/weekly cleaning.

Use STONE DEGREASER™ for stain spot cleaning and periodical cleans.

CLEAN UP

Thoroughly rinse application equipment with methylated/ white spirits or solvents.

DISPOSAL

CONSERVE & SEAL™ must be disposed of according to local, state and federal regulations.

SAFTEY NOTES

For more specific and further information regarding the handling of this product, please refer to the Safety Data Sheet.

Premium Coatings Australia (PCA) warrants to the original consumer / purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of 52 weeks from the date of original purchase. PCA's sole liability under this warranty shall be limited to the replacement of the product. This warranty will not apply to any product which has been modified in any way or which has not been used in accordance to the manufacturer's instructions. This warranty does not cover product damaged before installation, mishandling, incorrect installation, normal wear and tear or incorrect cleaning / maintenance procedures. PCA makes no other warranties either expressed or implied. This warranty gives the purchaser specific legal rights and is not transferable.



**FORMULATED & MANUFACTURED
IN AUSTRALIA FOR
AUSTRALIAN CONDITIONS**

WWW.PREMIUMCOATINGS.COM.AU

1300 220 337 | sales@premiumcoatings.com.au | Unit 1C/62 Heathcote Road, Moorebank, NSW 2170