

PCA SurfaceShield® Pro - WL

SURFACESHIELD® PRO - 'WET LOOK' is a stable, V.O.C. compliant deep penetrating enhancing sealer providing excellent water repellency and stain resistance to substrates.

SURFACESHIELD® PRO - 'WET LOOK' will not flake, peel, yellow, crack or blister. It highlights features of the natural stone and enhances dull/old looking stone while allowing the surfaces to breathe. It can be used to treat most natural stone surfaces such as:

- | | | |
|--|---|---|
| <input checked="" type="checkbox"/> MARBLE | <input checked="" type="checkbox"/> GRANITE | <input checked="" type="checkbox"/> CONCRETE |
| <input checked="" type="checkbox"/> TRAVERTINE | <input checked="" type="checkbox"/> SOME UNGLAZED TILES | <input checked="" type="checkbox"/> BLUESTONE |
| <input checked="" type="checkbox"/> LIMESTONE | <input checked="" type="checkbox"/> SLATE | |
| <input checked="" type="checkbox"/> SANDSTONE | <input checked="" type="checkbox"/> BASALT | |



- Provides a rich 'Wet Look' colour
- Internal and external use
- High stain resistance
- Allows surface to breathe
- Does not alter slip resistance
- Oil and water repellent
- Highlight features of Natural Stone

WHERE NOT TO USE

Glazed and some very low porosity tiles.

For the above surfaces please contact PCA's office on 1300 220 337 for an alternative product suggestion

Always do a test first in an inconspicuous area to ensure suitability and satisfactory results.

EXPECTED WEAR

SURFACESHIELD® PRO - 'WET LOOK' can last up to 15 years under normal conditions and following suggested maintenance guidelines. Extreme weather conditions, harsh cleaning methods and the use of high alkaline, ammonia, caustic, acid or solvent based cleaners, bleach or abrasive scrubbing pads will affect the long term performance of the sealer. It is recommended that heavy traffic areas should be tested yearly and product reapplied if necessary.

LIMITATIONS / INSTRUCTIONS

Do NOT use for any non-recommended surfaces. SURFACESHIELD® PRO - 'WET LOOK' will darken stone surfaces. SURFACESHIELD® PRO - 'WET LOOK' will not prevent surface wear and scuff marks or surface etching from acids or caustic chemicals.

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a minimum 24 hour cure time to determine ease of application and desired results.

Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, free of waxes, coatings, and previous sealers, and is completely dry.

Surface must remain dry and free from moisture for the entire cure period. Surface temperature should be between 10°C and 26.7°C. Ensure that the area is well ventilated during application and until the surface is dry. Keep children and pets out of the area until treated surface is dry.

SURFACE PREPARATION AND APPLICATION / DIRECTION FOR USE

Surfaces should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence and laitance before applying SURFACESHIELD® PRO - 'WET LOOK'. If strong acidic or caustic cleaners are used, neutralise the surface with a diluted solution of STONE DEGREASER™, thoroughly and completely wash/rinse to remove any residues.

1. Ensure the surface is clean and dry.
2. Any existing stains must be removed prior to sealant application.
3. Cover surfaces not intended to be treated.
4. Apply an even first coat using a roller, brush, or solvent resistant pump sprayer allowing to sealer to penetrate for 5-10 minutes, thoroughly wipe all excess sealer with clean and absorbent towels.
5. If more coats are required on porous surfaces, please repeat step 4.
6. After final application, thoroughly wipe all excess sealer with clean and absorbent towels. Do not allow excess sealer to dry on the surface
7. A full cure is achieved in 48 – 72 hours. Avoid Foot traffic for a min of 24 hours.
8. It is important that no water comes into contact with newly sealed surfaces for at least 24 hours after application.
9. Clean tools used during application with methylated spirits/solvents. Rags and equipment that are wet with the product may be flammable.

COVERAGE

Application rate depends on porosity of the tile or paver, temperature and method of application and ranges between 4 – 15 SQMs per litre. USE AS IS, DO NOT DILUTE

MAINTENANCE

Use STONE SOAP™ for daily/weekly cleaning.

Use STONE DEGREASER™ for stain spot cleaning and periodical cleans.

CLEAN UP

Thoroughly rinse application equipment with solvent.

DISPOSAL

SURFACESHIELD® PRO - 'WET LOOK' must be disposed of according to local, state and federal regulations.

SAFTEY NOTES

For more specific and further information regarding the handling of this product, please refer to the Safety Data Sheet.

Premium Coatings Australia (PCA) warrants to the original consumer / purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of 52 weeks from the date of original purchase. PCA's sole liability under this warranty shall be limited to the replacement of the product. This warranty will not apply to any product which has been modified in any way or which has not been used in accordance to the manufacturer's instructions. This warranty does not cover product damaged before installation, mishandling, incorrect installation, normal wear and tear or incorrect cleaning / maintenance procedures. PCA makes no other warranties either expressed or implied. This warranty gives the purchaser specific legal rights and is not transferable.



**FORMULATED & MANUFACTURED
IN AUSTRALIA FOR
AUSTRALIAN CONDITIONS**

WWW.PREMIUMCOATINGS.COM.AU

1300 220 337 | sales@premiumcoatings.com.au | Unit 1C/62 Heathcote Road, Moorebank, NSW 2170